


- SURFACE OF JOINT MUST BE SMOOTH AND FREE FROM DIRT AND LAITANCE BEFORE FIXING WATERSTOP.
- WATERSTOP MUST BE GLUED TO THE SURFACE WITH RECOMMENDED ADHESIVE.

Hycrete details illustrate generic construction guidelines. They are intended for use by design/construction professionals, to assist in developing project-specific details. These should be modified where necessary to accommodate individual project conditions. The user maintains all responsibility for verifying the applicability and suitability of the technical service or information provided. Contact a Hycrete technical professional for assistance in project-specific requirements. Always refer to project specifications and local building codes for any special requirements.
 © 2009 Hycrete, Inc. All rights reserved. The right to utilize Hycrete details for commercial purposes is granted exclusively to contractors, architects, quantity surveyors, engineers, waterproofing consultants, and specification writers. Hycrete™ is a registered trademark of Hycrete, Inc.

LOCATION: ABOVE OR BELOW GRADE	DETAIL TYPE: SLAB OR WALL		
POUR TYPE:CIP OR SHOTCRETE	APPLICATION: ALL APPROVED APPLICATIONS		
 Delivering Concrete Solutions	DRAWING TITLE: LINK SEAL WALL OR SLAB DETAIL.		
	462 BARELL AVENUE CARLSTADT NJ 07072 USA +1 (201) 386 8110 WWW.HYCRETE.COM	SEP 2009	DRAWING NUMBER: 7078001
		DRWN BY:FAZAL	NTS
		CHKD BY:NHM	