

- SURFACE OF JOINT MUST BE SMOOTH AND FREE FROM DIRT AND LAITANCE BEFORE FIXING WATERSTOP.
- WATERSTOP MUST BE GLUED TO THE SURFACE WITH RECOMMENDED ADHESIVE.

Hycrete details illustrate generic construction guidelines. They are intended for use by design/construction professionals, to assist in developing project—specific details. These should be modified where necessary to accommodate individual project conditions. The user maintains all responsibility for verifying the applicability and suitability of the technical service or information provided. Contact a Hycrete technical professional for assistance in project—specific requirements. Always refer to project specifications and local building codes for any special requirements.

© 2009 Hycrete, Inc. All rights reserved. The right to utilize Hycrete details for commercial purposes is granted exclusively to contractors, architects, quantity surveyors, engineers, waterproofing consultants, and specification writers. Hycrete Two is a registered trademark of Hycrete, Inc.

	LOCATION: ABOVE GRADE	DETAIL TYPE: PLAZA, PODIUM OR ELEVATED SLAB
	POUR TYPE: CIP	APPLICATION:
ls,	Hycrete	ELEVATED SLAB OVER UNOCCUPIED SPACE.
		DRAWING TITLE: PLAZA OR PODI UM DECK/ PARAPET
ıts.	Delivering Concrete Solutions	WALL JOINT DETAIL

SEP 2009

DRWN BY:FAZAL

CHKD BY:NHM

DRAWING NUMBER

7201002 NTS

Delivering Concrete Solutions

462 BARELL AVENUE CARLSTADT NJ 07072 USA +1 (201) 386 8110 WWW.HYCRETE.COM